

Sonos LED Beacon

A general purpose beacon for fire, security and industrial applications.

With the TimeSaver base, connections are made to the base during the initial wiring phase which results in faster and more reliable installation. The beacon head 'twists and clicks' into the base on commissioning, avoiding the wiring and connection problems associated with traditional sounders.

Deep base units have weatherproof protection to IP65 and can be used in all locations both indoors and outdoors.

The Sonos Beacon utilises a full faced, translucent sounder case which provides a much larger lens and a greater spread of light.

Sonos Beacon units have a red colour base as standard and a red lens.



Features

- Low current LED beacon
- Simple 'First Fix' installation (no second fix wiring)
- Quick connect/disconnect
- Weatherproof to IP65 (Deep base units)
- High efficiency LED beacon consumes less than 5mA

Specification

IP Rating	IP65 (Deep base)
Rating	Continuous
Frequency	400-2850Hz
Operating Temp	-25°C to +70°C
Construction	Flame Retardant Polycarbonate
Voltage	17-60 V DC
Current	5mA
Cable Entries	Deep Basse: 2 * 20mm cable glands
Weight	215g (Shallow base) 250g (Deep base)

Order Codes and Options

08-PSB-0009:	Sonos LED beacon with Red lens and shallow base
08-PSB-0017:	Sonos LED beacon with Red lens and deep base

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle, NE12 8EW, UK T: +44 (0)845 894 7000, E: enquiries@advancedco.com, W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.