

Loop Powered Sounder Beacon Base

The loop driven sounder beacon base series is a loop driven device designed around a fully digital protocol.

The sounder beacon base is an acoustic output device which supports up to 32 tones ranging from a slow whoop, pulsed and continuous tone with synchronisation of both the sounder and beacon.

The device has four fixed volume levels ranging from 85 dB to a maximum of 92dB making the device suitable for almost any EN markets.

The low profile sounder is designed to comply with EN54 and requires the 20-VPU1000-ADV hand held programmer for volume and operating mode configuration.

The sounder beacon base provides a fast and secure response, and incorporates a bidirectional short circuit isolator.

Features

- 32 programmable tones
- Compatibility mode for standard loop sounders
- Loop driven
- Soft and safe addressing
- Large cable entry
- Low profile design
- Synchronisation of flashes
- 84.5 dB to 92.5 dB

Specification

Power Supply	18V to 40V DC
Standby Current Consumption	70µA
Humidity (non condensing)	90% RH
Operating Temperature Range	-30°C to +70°C
Dimensions (Width x Depth)	160 x 60mm
Weight	300 grams
Applicable Wire Gauge	0.5mm ² to 2.5mm ²
Volume Setting	
Low	Load: 4.5mA Volume: 84.5dB
Medium	Load: 4.8mA Volume: 88.9dB
High	Load: 5.6mA Volume: 90.3dB
Extra High	Load: 7.7mA Volume: 92.5dB
IP Rating	21C

Order Codes and Options

20-VBLS100AV/32-ADV:	Loop Powered Sounder Beacon Base
----------------------	----------------------------------

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle, NE12 8EW, UK T: +44 (0)845 894 7000, E: enquiries@advancedco.com, W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.