

## Waterproof Call Point

The Axis Resettable Call Point is a loop powered device designed around a fully digital protocol.

A unique manual call point that mimics the feel of breaking glass whilst offering the user the benefits and environmental advantages of a re-settable operating element.

Upon activation an indicator drops into view at the top of the window. The unit is then simply reset by use of a special key.

The same special key is used for removal of the device's front cover.

The unit provides a fast and secure response, and incorporates a bidirectional short circuit isolator.

Connections are made using plug-in terminal blocks which will accept conductors up to 2.5mm<sup>2</sup>.



### Features

- Short circuit isolators in each device to the requirements of EN54-17
- Large capacity, up to 240 devices per loop
- Auto addressing capability by the control panel or manually using a handheld programmer (20-VPU1000-ADV)
- Digital checking of double address
- Line quality information
- Bicolour (red green) LED driven by the control panel

### Specification

Power Supply	15-40 V
Average Current Consumption	I=70 uA
LED Current Consumption	Iled=6mA @24Vdc
Operating Temperature Range	-20°C / +70°C
Dimensions H x W x D mm	119 x 128 x 62
IP Rating	67

### Order Codes and Options

20-VWCP100-ADV:	AV Waterproof Call Point
-----------------	--------------------------

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle, NE12 8EW, UK T: +44 (0)845 894 7000, E: [enquiries@advancedco.com](mailto:enquiries@advancedco.com), W: [www.advancedco.com](http://www.advancedco.com)

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.