

## DIN Rail Mount Monitored Output Module

The Axis single output modules are loop powered, designed around a fully digital protocol and provides control by closing contacts of auxiliary devices such as fire shutters.

The output channel is monitored and will detect Open and Short circuit conditions.

The unit provides a fast and secure response, and incorporates a bidirectional short circuit isolator.

Connections are made using plug-in terminal blocks which will accept conductors up to 2.5mm<sup>2</sup>.

The unit is suitable for fixing to a standard 35mm DIN rail.



### Features

- Short circuit isolators in each device to the requirements of EN54- 17
- Addressing using the Device Programming Tool or Auto addressing capability via the fire control panel.
- Auto addressing capability (Control panel feature)
- Digital checking of double address
- Line quality information
- Bicolour (red green) LED driven by the control panel

### Specification

Power Supply	15-40 V
Average Current Consumption	I=120 uA
LED Current Consumption	Iled=6mA @24Vdc
Operating Temperature Range	-30°C / +70°C
Humidity (non condensing)	95% RH
Relay Switching Characteristic	I=2A V=30Vdc
End-of-line resistor	(Reol): 27Kohm
Dimensions H x W x D mm	79 x 90.5 x 25
Weight grams	80
IP Rating	21C

### Order Codes and Options

20-VMDC100-ADV:	AV DIN Rail Mount Monitored Output Module
-----------------	---

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle, NE12 8EW, UK T: +44 (0)845 894 7000, E: [enquiries@advancedco.com](mailto:enquiries@advancedco.com), W: [www.advancedco.com](http://www.advancedco.com)

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.