

Wall Mounting Single Relay Output Module

The Axis single channel output modules are loop powered, designed around a fully digital protocol and provides form C changeover contacts for control of auxiliary devices such as fire shutters.

The output channel is a normally de-energised relay switched on by a command from the control panel.

The unit provides a fast and secure response, and incorporates a bidirectional short circuit isolator.

Connections are made using plug-in terminal blocks which will accept conductors up to 2.5mm².

The unit is supplied fixed to a plate which is suitable for wall mounting with a choice of standard 25 mm or deep 47 mm mounting boxes available.



Features

- Short circuit isolators in each device to the requirements of EN54-17
- Auto addressing capability (by the control panel) or manually using a hand held programmer.
- Digital checking of double address
- Line quality information
- Bicolour (red/green) LED driven by the control panel

Specification

Power Supply	15-40 V
Average Current Consumption	I=120 uA
LED Current Consumption	I _{led} =6 mA @24 Vdc
Operating Temperature Range	-30°C / +70°C
Humidity (non condensing)	95% RH
Relay Switching Characteristic	I=2 A V=30 Vdc
Dimensions H x W x D mm	85 x 85 x 30
Weight grams	200
IP Rating	21

Order Codes and Options

20-VMC120-ADV:	Wall Mounting Single Relay Output Module
----------------	--

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle, NE12 8EW, UK T: +44 (0)845 894 7000, E: enquiries@advancedco.com, W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.