

Wireless Heat Detector

The Axis Wireless Heat Detector has been designed to fully meet the requirements of European Standard EN54-5 and EN54-25. The detector has the same low profile mechanical design as that of the hard wired 20-V350-ADV device.

Each device is powered using low-cost lithium batteries. Both primary and secondary batteries are continuously monitored for low battery condition which is indicated by an internal LED as well as a fault condition being displayed at the translator module and the fire control panel.

Each detector will automatically adjust its frequency and manage its power radiation in accordance with the signal quality received from the Axis wireless translator module.

Bi-directional communications with the wireless translator is based on a proven protocol and wireless technology and is fast, reliable and provides the highest level of security.

The wireless communications operate on the frequency of 433 MHz.



Features

- Bi-directional communication protocol between all wireless devices
- Rapid, cost effective installation with minimal disturbance
- Fully Intelligent devices
- Up to 32 wireless devices allowed with each translator
- Fully Monitored Primary and Secondary Power Source

Specification

Communication range with the 20-VW2W100-ADV or 20-SGWE100-ADV

Up to 200 m (in open space)

Operating frequency

433.05 MHz - 434.79 MHz

Modulation type

FSK

Operating frequency channels

7

Radiated power

5 dBm (3 mW) typical

Transmission message period

60 sec default

Main battery

Type CR123A 6.5 years typical

Secondary battery

Type CR2032A 2 months typical

Dimensions

110 mm x 54 mm

Weight

150 g Without Batteries

Operating temperature range

From -30 °C to +55 °C. From -10 °C to +55 °C with secondary battery

IP Rating

42 with WP100 silicon protection, 40 without

Order Codes and Options

20-SG350/433-ADV:

Wireless Heat Detector

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle, NE12 8EW, UK T: +44 (0)845 894 7000, E: enquiries@advancedco.com, W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.