

Standard Network Booster

The Mxp-030 network booster provides optical isolation between Axis EN series control panels and the remainder of the network. Used in this manner, the Mxp-030 extends the distance of an existing network and allows expansion beyond the 32 node limitation when using standard network card.

The unit is supplied pre-configured for ease of installation, allowing for quick and trouble-free extension of the existing network.

Features

- Extends network up by to 1.2Km
- Allows more than 32 nodes with standard network card
- Wide operating voltage available
- Low current consumption

Specification

Input voltage	10 - 30Vdc
Isolation	2KV RMS for 1 minute via optical isolation
Current consumption	67mA @ 12Vdc
Signal and power connection	Via terminal block
operating temperature	-40 to +80 degrees C
Operating humidity	0 to 95% non-condensing
LED indication	2 x data flow
Dimensions	100 x 74 x 23 mm
Din rail mounting	35mm top hat

Limitations

Requires external 10-30Vdc power supply (Not included) but can be powered from an MxPro control panel

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle, NE12 8EW, UK T: +44 (0)845 894 7000, E: enquiries@advancedco.com, W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.