

## Enhanced Relay Output Module

The Relay Output Module is a loop-powered device which incorporates a 240 V rated volt-free relay output. The module can be used outdoors if mounted in a suitable weatherproof enclosure.

### Features

- Built-in isolator
- Visible LEDs
- Loop powered
- Improved design for ease of wiring
- Communicates with XP95 and Discovery protocols

### Listings and Approvals

- UL, ULC, SII and CSFM



### Specification

#### General\*

Product Operating Temperature	32° to 120° F
Humidity	10% to 93% RH (no condensation or icing)
Standards and Approvals	UL, ULC, SII, CSFM
Dimensions	4.9" W x 4.9" H x 1.175" D
Materials	Housing UL94 V-0 polycarbonate
Wire Size	12-24 AWG

#### LED Status

LED Colour:	Polling
Green	Isolation
Yellow (solid)	

#### Single Line Circuit (SLD) - Supervised Power Limited

Supply Voltage	17 V to 28 VDC
Modulation Voltage	5 V to 9 V peak to peak
Supervisory Current	500 $\mu$ A
Switch-on Surge Current	900 $\mu$ A
Alarm/Operated Current, LED On	1.6 mA per LED
Maximum Loop Current	1 A
Relay output	Non-supervised Programmable Dry contact 30 V DC - 4 A - resistive 240 V AC - 4 A - resistive

## Output Circuit

Relay output	Non-supervised Programmable Dry contact 30 V DC - 4 A - resistive 240 V AC - 4 A - resistive
--------------	--

NB All data is supplied subject to change without notice. Specifications are typical at 24 V, 73° F and 50% RH unless otherwise stated.

## Order Codes and Options

SA4705-701ADV

Enhanced Relay Output Module

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK **T:** +44 (0)345 894 7000, **E:** [enquiries@advancedco.com](mailto:enquiries@advancedco.com),  
**W:** [www.advancedco.com](http://www.advancedco.com)

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.