

Conventional Class B Heat Detector

The Conventional Class B Heat Detector is a cost effective and aesthetically pleasing, non-addressable fixed temperature heat detector.

These detectors are designed for open area protection and provide the best warning of fire in locations which are not suitable for smoke detection technologies.

A centrally positioned LED indicator provides 360° visibility of detector activation and an in-built magnet test feature allows easy activation to verify operation of the detectors.

A custom ASIC provides superior and reliable detection performance whilst reducing the problems of false alarms.



Approvals

- EN54-5:2000 +A1:2002
- Approved by BRE/LPCB and certified by the UAE Civil Defence

Features

- Central LED providing 360° visibility.
- Magnetic test.
- Anti-tamper locking feature.
- Robust and reliable.
- 3 year warranty.

Specification

Operating Voltage	10-30V DC
Average standby current	60 uA @ 24V DC
Maximum allowed alarm current	40mA (externally limited)
Maximum allowed remote device current	20mA (externally limited)
High temperature alarm threshold (class B)	78°C
Operating Temperature Range	-30°C / +70°C
Humidity (no condensation)	95% RH
Dimensions (with base)	110 x 54 mm

Order Codes and Options

20-AS3500/B-ADV:	Conventional Class B Thermal Detector
------------------	---------------------------------------

20-ABR100-ADV:	Universal resistor base
----------------	-------------------------

20-ABDR100-ADV:	Universal resistor + diode base
-----------------	---------------------------------

20-ABSR100-ADV:	Deep resistor base
-----------------	--------------------

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK **T:** +44 (0)345 894 7000, **E:** enquiries@advancedco.com,
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.