

## Conventional Resettable Manual Call Point

The Resettable Call Point is a unique manual call point that mimics the feel of breaking glass whilst offering the user the benefits and environmental advantages of a re-settable operating element.

The 'ReSet' uses a simple yet ingenious patented mechanism which consists of a rigid plastic operating element and an over centre spring mechanism. This arrangement provides real action on operation and simulates break glass activation.

An activation indicator drops into view at the top of the window after the 'ReSet' has been operated. The unit is then simply reset with a key and is ready for re-use straight away.

### Applications

The 'ReSet' call point is compatible with most conventional fire alarm systems. It is safe for use in areas where glass cannot be used, e.g. food processing plants and swimming/leisure centres.

As the unit can be simply reset it provides an ideal solution for areas that suffer from a high number of false activations such as schools, shopping centres and other public places.

Two options are available

- **Series 01** - Conventional Fire Model with 470 & 680 Ohm internal resistors. Available in Red only
- **Series 02** - Single Pole Changeover. Available in Yellow, White, Green, Orange



### Approvals

- EN54-11 - Series 01 only

### Features

- Glass appearance maintains operator deterrence
- Positive activation that mimics the feel of breaking glass
- Visible warning flag confirms activation
- Simple key to reset operating element - no broken glass
- No glass elements to break, loose or incorrectly fit during installation
- Complete functional test with every activation
- Extremely attractive, high value look and feel
- Built to meet requirements of IP2X

## Specification

Current Rating	<ul style="list-style-type: none"> <li>All Series: 1 Amp 12-24V DC</li> <li>Series 02: 3 Amps 125 - 250V AC</li> </ul>
Built-in Resistor Values (Series 01 only)	470Ω (R1) and 680Ω (R2)
Housing and Mounting Box Material	Polycarbonate
Electrical Contact Material	Silver Plated Brass
Operating Temperature	-20°C to +65°C
Installation Terminal Conductor Size	0.5mm - 2.5mm
Colours	<ul style="list-style-type: none"> <li>Red (Series 01)</li> <li>Yellow, White, Green, Orange (Series 02)</li> </ul>
Mounting	Dual mount, for flush- or surface-mount with back box
Dimensions	87 x 87 x 23mm (flush-mount) or 87 x 87 x 58mm (surface-mount)

## Order Codes and Options

08-RP-RD2-01	ReSet Manual Call Point - Red (Series 01) with 'House Flame' logo. Dual mount (Surface or Flush)
08-RP-GD2-02	Re Set Manual Call Point - Green (Series 02) with 'Running Man' logo. Dual mount (Surface or Flush)
08-RP-YD2-02	Re Set Manual Call Point - Yellow (Series 02) with self-assemble label. Dual mount (Surface or Flush)
08-RP-WD2-02	Re Set Manual Call Point - White (Series 02) with self-assemble label. Dual mount (Surface or Flush)
08-RP-OD2-02	Re Set Manual Call Point - Orange (Series 02) with self-assemble label. Dual mount (Surface or Flush)
08-RP-K/10	Spare ReSet Key (pack of 10) - Black

### Self-assemble Label options

EMERGENCY
EMERGENCY DOOR RELEASE
EMERGENCY EXIT
EVACUATE
GAS ABORT
GAS RELEASE
GAS SHUT OFF
INCIDENT
ISOLATION SWITCH
PANIC ALARM
POOL ALARM
SMOKE VENT

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK T: +44 (0)345 894 7000, E: [enquiries@advancedco.com](mailto:enquiries@advancedco.com),  
W: [www.advancedco.com](http://www.advancedco.com)

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.