

Sonos LED Beacon

A general purpose beacon for fire, security and industrial applications.

With the TimeSaver base, connections are made to the base during the initial wiring phase which results in faster and more reliable installation. The beacon head 'twists and clicks' into the base on commissioning, avoiding the wiring and connection problems associated with traditional sounders.

Deep base units have weatherproof protection to IP65 and can be used in all locations both indoors and outdoors.

The Sonos Beacon utilises a full faced, translucent sounder case which provides a much larger lens and a greater spread of light.

Sonos Beacon units have a red colour base as standard and a red lens.



Features

- High output LED beacon for bright notification
- Simple 'First Fix' installation (no second fix wiring)
- Weatherproof to IP65 (deep base units)
- Synchronised flash

Specification

| | |
|----------------|---|
| IP Rating | IP21 (Shallow base), IP65 (Deep base) |
| Operating Temp | -25°C to +65°C |
| Construction | Flame Retardant Polycarbonate |
| Voltage | 10-60 V DC |
| Current @24V | 55mA |
| Cable Entries | 2 x 20mm cable glands (Deep base) |
| Weight | 0.22kg (Shallow base), 0.25kg (Deep base) |

Order Codes and Options

| | |
|--------------|---|
| 08-PSB-0221: | Sonos LED beacon with Red lens and shallow base |
| 08-PSB-0226: | Sonos LED beacon with Red lens and deep base |

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK T: +44 (0)345 894 7000, E: enquiries@advancedco.com, W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.