

Sonos Sounder Beacon

A general purpose electronic sounder for fire, security and industrial applications; the Sonos Sounder Beacon is certified to EN54.

With the TimeSaver base, connections are made to the base during the initial wiring phase which results in faster and more reliable installation. The sounder head 'twists and clicks' into the base on commissioning, avoiding the wiring and connection problems associated with traditional sounders.

With a choice of 32 tones including all the major international standards, the Sonos Sounder Beacon has universal acceptance.

The Sonos Sounder Beacon utilises a full faced, translucent sounder case rather than a separate add-on beacon giving a much larger lens and a greater spread of light.



Features

- Low current LED beacon
- Simple 'First Fix' installation (no second fix wiring)
- No locking screw required
- Tone and volume can be preset adjusted off-base - 20dB
- Waterproof to IP65 (Deep base units)
- Sounder and beacon can be controlled separately
- LPCB, VDS and NF approved

Specification

IP Rating	IP65 (Deep base)
Rating	Continuous
Frequency	400-2850Hz
Operating Temp	-25°C to +70°C
Construction	Flame Retardent Polycarbonate
Audibility at 1M Tones (Tone dependent)	Up to 106dB (A)
Voltage	9-60 VDC
Tones	32
Current	Sounder: 4-45mA. Beacon: 5mA
Cable Entries	Deep Base: 2 * 20mm cable glands
Weight	215g (Shallow base) 250g (Deep base)
Compliance	EN54-3 Type A (Shallow base) EN54-3 Type B (Deep base)

Order Codes and Options

08-PSC-0002:	Sonos sounder beacon with Red lens (PSS-0068) with shallow Red base (PSO-0001)
08-PSC-0013:	Sonos sounder beacon with Red lens (PSS-0068) with deep Red base (PSO-0003)

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK T: +44 (0)345 894 7000, E: enquiries@advancedco.com, W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.