

Wireless Input Module

The Axis Wireless Input Module allows supervision of an external device providing on/off status information to the control panel via an AV wireless translator module. Each module is intended to interface between a control panel and normally open contact devices. The connection between the module and the external device is supervised with the aid of an end of line resistor.

Each device is powered using low cost lithium batteries. Both primary and secondary batteries are continuously monitored for low battery condition which is indicated by an internal LED as well as a fault condition being displayed at the translator module and the fire control panel.

Each module will automatically adjust its frequency and manage its power radiation in accordance with the signal quality received from the Axis wireless translator module.

Bi-directional communications with the wireless translator is based on a proven protocol and wireless technology and is fast, reliable and provides the highest level of security.

The wireless communications operates on the European recommended frequency of 868 MHz and conforms to the European Standard EN54-25.

Features

- Bi-directional communication protocol between all wireless devices
- Rapid, cost effective installation with minimal disturbance
- Fully Intelligent devices
- Up to 32 wireless devices allowed with each translator
- Fully Monitored Primary and Secondary Power Source

Specification

Communication range	Up to 200 m (in open space)
Operating frequency	868.15 MHz - 869.85 MHz
Modulation type	FSK
Operating frequency channels	7
Radiated power	5 dBm (3 mW) typical
Transmission message period	60 seconds default
End of Line Resistor	(Reol) 5.6Kohm
Alarm Resistor	2.2Kohm
Main battery	Type CR123A 6.5 years typical
Secondary battery	Type CR2032A 2 months typical
Dimensions H x W x D mm	110 x 54
Weight grams	150 g Without Batteries
Operating temperature range	From -30°C to +55°C From -10°C to +55°C with secondary battery
IP Rating	65

Order Codes and Options

20-SGMI100-ADV:	Wireless Input Module
-----------------	-----------------------

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK **T:** +44 (0)345 894 7000, **E:** enquiries@advancedco.com,
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.