

## Addressable Beacon

The Axis beacon is a loop powered addressable device designed around a fully digital protocol.

The device has a low current consumption and low profile design which allows easy and fast installation. The beacon can also be secured to the base by a locking screw.

The beacons flash rate and light intensity can be selected by a DIP switch.

Each unit provides a fast and secure response, and incorporates a bidirectional short circuit isolator.



### Features

- Short circuit isolators in each device to the requirements of EN54-17
- Large capacity, up to 240 devices per loop
- Auto addressing capability (by the control panel) or manually using 20-VPU1000-ADV handheld programmer
- Digital checking of double address
- Line quality information

### Specification

Power Supply	15-40 V
Standby current @ 24 V	70uA
Wire gauge range for the terminals	0.5 - 2.5 mm <sup>2</sup>
Current consumption range @ 24V (beacon's selected settings)	min 3mA (0.5Cd and 1Hz) max 6mA (1Cd and 0.5Hz)
Light output intensity range (user selectable)	0.5 - 1 Cd
Flash rate range (user selectable)	0.5 - 1 Hz
Operation environmental temperature range	-10°C - +55°C
Operation environmental humidity range	5% - 95% RH
IP rating	21C
Dimensions H x W x D mm	93 x 53
Weight grams	110
IP Rating	21C

### Order Codes and Options

20-VLBE100-ADV:	AV Addressable Beacon
-----------------	-----------------------

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK T: +44 (0)345 894 7000, E: [enquiries@advancedco.com](mailto:enquiries@advancedco.com), W: [www.advancedco.com](http://www.advancedco.com)

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.