

Wireless Expander - obsolete

The Axis Wireless Expander is an externally powered module that supports the Axis Wireless Translator module. The Expander module provides the ability to communicate with wireless devices over greater distances and in difficult radio environments.

The Axis Wireless system utilises a unique and powerful 'Microcell' architecture with a capacity of up to 7 Expanders and 32 wireless devices per translator module. Wireless devices can be any combination of detectors, call points, sounders or input and output modules.



Features

Specification

Communication range	Up to 600 meters (in open space)
Communication range with other wireless devices	Up to 200 meters (in open space)
Operating frequency	433.05 MHz - 434.79 MHz
Modulation type	FSK
Operating frequency channels	7
Radiated power	5 dBm (3 mW) typical
Transmission message period	12 seconds default
Power supply voltage range	From 9 V to 27 V
Current consumption	85 mA @ 12 Vdc
Dimensions H x W x D mm	120 x 160 x 51 w/o antennas
Weight grams	330 g
Operating temperature range	From -30°C to +50°C
Antennas	Two External, in orthogonal configuration
Primary and backup power supply voltage's lower fault threshold	11 +/- 0.5 V
IP Rating	51C

Order Codes and Options

20-SGWE100/433-ADV:	Wireless Expander
---------------------	-------------------

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK T: +44 (0)345 894 7000, E: enquiries@advancedco.com, W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.