

Resettable Manual Callpoint - obsolete

The Resettable Call Point is a unique manual call point that mimics the feel of breaking glass whilst offering the user the benefits and environmental advantages of a resettable operating element. It is compatible with most conventional fire alarm systems. They are safe to use in areas where glass cannot be used such as schools, shopping centres and other public places. As the unit can be simply reset, it also provides an ideal solution for areas that suffer from a high number of false activations such as schools, shopping centres and other public places.

The 'ReSet' uses a simple yet ingenious patented mechanism which consists of a rigid plastic operating element and an over centre spring mechanism. This arrangement provides real action on operation and simulates break glass activation.

An indicator drops into view at the top of the window on activation. The unit is then simply reset with a key and is ready for re-use straight away.

The Call Point has an attractive, high value look and feel: glass appearance maintains operator deterrence, whilst a visible warning flag confirms activation.

Installation

Easy installation due to no glass elements that could be broken or incorrectly fitted. The Call Point can be flush or surface mounted.



Features

- EN54-11 Approved
- Glass appearance maintains operator deterrence
- Positive activation that mimics the feel of breaking glass
- Visible warning flag confirms activation
- Simple key to reset operating element - no broken glass
- No glass elements to break, loose or incorrectly fit during installation
- Complete functional test with every activation
- Extremely attractive, high value look and feel
- Low profile, heavy duty terminations - two built-in resistor values
- Available in Red and Yellow
- Optional integral cover can be fitted to prevent accidental activation.
- Low profile, heavy-duty terminations

Specification

Current Rating	3 Amps 12-24V _{DC}
Housing and Mounting Box Material	Polycarbonate
Electrical Contact Material	Silver Plated Brass
Operating Temperature	-10°C to +55°C
Installation Terminal Conductor Size	0.5mm - 2.5mm
Humidity (no condensation)	0 to 95%
Colours	Red and Yellow
Mounting	Flush or surface with back box
Dimensions - flush	87 H x 87 W x 23 D
Dimensions - surface	87 H x 87 W x 58 D
Approvals	EN54-11 Approved

Order Codes and Options

RED	
08-RP-RF2-01	Red Flush Mounted only (series 01 - NO 470R & 680R) EN54-11 with 'House Flame' logo
08-RP-RD2-01	Red Dual mount (series 01 - NO 470R & 680R) EN54-11 with 'House Flame' logo
08-RP-RS2-01	Red Surface mount only (series 01 - NO 470R & 680R) EN54-11 with 'House Flame' logo
YELLOW	
08-RP-YF2-02	Yellow Flush Mount only (Series 02 - SPCO) with 'Gas Release' text
08-RP-YD2-02	Yellow Dual Mount (Series 02 - SPCO) with 'Gas Release' text
08-RP-YS2-02	Yellow Surface Mount only (Series 02 - SPCO) with 'Gas Release' text
08-RP-YF2-11	Yellow Flush Mount only (Series 11 - 2 x SPCO) with 'Gas Release' text
08-RP-YD2-11	Yellow Dual Mount (Series 11 - 2 x SPCO) with 'Gas Release' text
08-RP-YS2-11	Yellow Surface Mount only (Series 11 - 2 x SPCO) with 'Gas Release' text
OTHER COLOURS	
08-RP-WD2-02	White Dual Mount (SPCO) with 'Panic Alarm' text
08-RP-GD2-02	Green Dual Mount (SPCO) with 'Running Man' logo
ACCESSORY	
08-RP-K/10	Spare Reset key (pack of 10) - Black

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK T: +44 (0)345 894 7000, E: enquiries@advancedco.com,
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.