

## Wireless Heat Enhanced Photoelectric Smoke Detector - obsolete

The Axis Wireless Heat Enhanced Photoelectric Smoke Detector has been designed to meet the European Standard EN54-5 and EN54-7 directives. The detector has the same low profile mechanical design as that of the hard wired AV Multicriteria Detector and incorporates the same advanced features such as a unique symmetrical smoke chamber, double dust trap and a continuous insect screen.

Each device is powered using low cost lithium batteries. Both primary and secondary batteries are continuously monitored for low battery condition which is indicated by an internal LED as well as a fault condition being displayed at the translator module and the fire control panel.

Each detector will automatically adjust its frequency and manage its power radiation in accordance with the signal quality received from the Axis wireless translator module.

Bi-directional communications with the wireless translator is based on a proven protocol and wireless technology and is fast, reliable and provides the highest level of security.

The wireless communications operates on the European recommended frequency of 868 MHz and conforms to the European Standard EN54-25.



### Features

- Bi-directional communication protocol between all wireless devices
- Rapid, cost effective installation with minimal disturbance
- Fully Intelligent devices
- Up to 32 wireless devices allowed with each translator
- Fully Monitored Primary and Secondary Power Source

### Standards and Approvals

- EN54-5:2000 +A1:2002
- EN54-7:2000 +A1:2002 +A2:2006
- EN54-25:2008
- Approved by BRE/LPCB and certified by the UAE Civil Defence

### Specification

Communication range	Up to 200 m (in open space)
Operating frequency	868.15 MHz - 869.85 MHz
Modulation type	FSK
Operating frequency channels	7
Radiated power	5 dBm (3 mW) typical
Transmission message period	60 seconds default
Main battery	Type CR123A 6.5 years typical
Secondary battery	Type CR2032A 2 months typical
Dimensions H x W x D mm	110 x 54
Weight grams	150 g Without Batteries
Operating temperature range	From -30°C to +55°C From -10°C to +55°C with secondary battery
IP Rating	42 with WP100 silicon protection, 40 without

## Order Codes and Options

20-SG200-ADV:

Wireless Heat Enhanced Photoelectric Smoke Detector

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK **T:** +44 (0)345 894 7000, **E:** [enquiries@advancedco.com](mailto:enquiries@advancedco.com),  
**W:** [www.advancedco.com](http://www.advancedco.com)

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.