

Wireless Sounder Base with Visual Indicator - obsolete

The Wireless Sounder Base with Visual Indicator activates its output when ordered to do so by the control panel in the event of a fire alarm. The activation command is sent from the control panel to the base sounder through the wire to wireless translator interface module and other possible wireless expander modules.

Communication between the sounder base and the translator / expanders is obtained through the wireless, analogue-intelligent bidirectional Axis EN protocol. The device's radio communication meets EN54-25.

The sounder is equipped with a supplementary visual indicator which reinforces the audible warning.

The wireless sounder base is designed to support the installation of Axis EN wireless detectors.



Features

- Up to 200 m communication range
- Approved to EN 54-25

Specification

Operating frequency range	868 MHz
Radiated power	5 dBm (3 mW)
Usable operating frequency channels	7
Radio signal's modulation type	FSK
Communication range	Up to 200 m in open space
Main and secondary battery types	CR123 A (3 V & 1.2 Ah)
Approved battery voltage range	2.75 v - 3.20 V
Alarm current	110 mA
Number of LEDs	Two - red and green
Operating temperature range	From -10°C to +55°C
Maximum tolerated humidity (no condensing)	95% RH
Maximum volume range @ 1m - selectable	between 70 dBa and 95 dBa at maximum volume depending on angle and tone selection
Device output tone's frequency range	440 Hz to 2900 Hz
IP rating	21
Dimensions	145 x 66 mm
Weight	260 g

Order Codes and Options

20-SGRBS100-AV-ADV:

Wireless Sounder Base with Visual Indicator

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK **T:** +44 (0)345 894 7000, **E:** enquiries@advancedco.com,
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.