Legacy Circu-Lite

The Circu-Lite offers both mains and emergency lighting in a simple but stylish luminaire with a white polycarbonate base and opal polycarbonate diffuser, sealed to IP65.

Installation

The Circu-Lite is supplied with a unique lever release for the diffuser which provides access to the control gear and lamp, which are mounted on a removable gear tray. The luminaires are available with mains only or switchable maintained operation. Non-maintained can be achieved by excluding the normal switched mains supply.

Operation

All emergency versions provide 3-hour duration as standard, from integral high-temperature nickel cadmium batteries. Maintained versions can be used for standard switched mains lighting but will automatically provide emergency lighting in the event of a complete loss of normal mains supply. Dali dimming controls can be added as an option.

The Circu-Lite fully complies to the requirements of EN60598.2.22. It also fully supports all the features of the LuxIntelligent range of emergency lighting test panels.

Features

- Decorative circular luminaire
- Standard and dimmable versions available
- Fully compatible with LuxIntelligent
- Fully complies with all aspects of EN60598.2.22

Specification

Supply voltage	230 Volts (220-240V) @ 50Hz
Light source	28W 2D
Supply current	Maintained:160mA
	Non-maintained:40mA
Battery	4.8V 4AHr
Recharge period	24 hours (14 hours 1-hour duration
Cable entry	20mm side entry, 13mm hole in rear
IP rating	IP65 Ta 25°C
Dimensions (mm)	330 (Diameter) x 126 (Height)

Order Codes and Options

UL28/M3/P:	Circu-Lite 28W 3 hour maintained addressable luminaire
UL28/AC:	Circu-Lite 28W mains-only luminaire
UL28/M3/P/Dali:	Circu-Lite 28W 3 hour maintained addressable luminaire with dali operation
UL28/AC/Dali:	Circu-Lite 28W mains-only luminaire with dali operation

Advanced, The Bridges, Balliol Business Park, Newcastle, NE12 8EW, UK T: +44 (0)1670 707 111 E: enquiries@luxintelligent.com W: www.luxintelligent.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.