

## Cine-Lite

Cine-Lite luminaires provide a simple solution to discrete exit signage. It is available as both maintained and non-maintained variations and comes with an opal down light panel to illuminate directly below the luminaire. In emergency, the lamp has a high 180 lumens output.

The Cine-Lite luminaires are constructed in black epoxy coated galvanised steel and are designed to reduce unwanted light emission. This makes it suitable for many applications, such as theatres, cinemas, school halls and discos.

The black opaque exit legend is hidden unless illuminated, making it not just ideal for exit directions, but also customised warnings only applicable under certain conditions, for example 'Do Not Enter'.

The luminaire fully complies with EN60598.2.22. Please note, the legend/pictogram itself is **not** compliant to BS 5499 Pt 4 or ISO 7010. Ultimately the premises where these Exit signs are fitted need to meet the requirements of the Regulatory Reform (Fire Safety) Order 2005 which is done by carrying out a fire-risk assessment. If the responsible person doing this risk assessment decides that a green on black sign is acceptable because of the reduced light levels in a particular area, then as long as this is documented and regularly reviewed this would mean that the premises is deemed to meet the requirements of the Order.

The luminaire fully supports all of the features of the LuxIntelligent range of emergency lighting test panels.



### Features

- Low light emissions when not required
- Complies with EN60598.2.22
- Fully supports LuxIntelligent testing panels

### Specification

Supply voltage	230Volt (220-240V) @ 50Hz
Supply current	Maintained:90mA Non-maintained:40mA
Lamp	8 Watt T5
Battery	3.6V 4AHr NiCd (250mA nominal charge current)
Recharge period	24 Hours (14 hours for 1 hour duration)
Cable entry	Back BESA entry
IP rating	IP20
Construction	Epoxy coated galvanised steel with polycarbonate legend
Dimensions (mm)	385 x 185 x 71 (L x W x H)

### Order Codes and Options

NLS8/M3/P-H:	Cine-Lite 8W 3 hour single-sided maintained addressable luminaire
NLS8/M3/P-H/AU:	Cine-Lite 8W 3 hour maintained luminaire with arrow up legend
NLS8/M3/P-H/AL:	Cine-Lite 8W 3 hour maintained luminaire with arrow left legend
NLS8/M3/P-H/AR:	Cine-Lite 8W 3 hour maintained luminaire with arrow right legend

NLS8/NM3/P-H:	Cine-Lite 8W 3 hour non-maintained luminaire with arrow down legend
NLS8/NM3/P-H/AU:	Cine-Lite 8W 3 hour non-maintained luminaire with arrow up legend
NLS8/NM3/P-H/AL:	Cine-Lite 8W 3 hour non-maintained luminaire with arrow left legend
NLS8/NM3/P-H/AR:	Cine-Lite 8W 3 hour non-maintained luminaire with arrow right legend

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle, NE12 8EW, UK T: +44 (0)1670 707 111, E: [enquiries@luxintelligent.com](mailto:enquiries@luxintelligent.com), W: [www.luxintelligent.com](http://www.luxintelligent.com)

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.