


The Ad-NeT network system allows all MxPro 5 series control panels, remote terminals and network peripherals to be connected together using standard fire resistant two-core cable. It provides both the benefits of distributed intelligence and reduced installation costs whilst catering for the smallest two-panel network through to the largest 200-panel wide area networked system.

The network operates as a true peer-to-peer system allowing information from any input or output device to be passed over the network and displayed on any MxPro 5 control panel or remote terminal as required.

Simply adding and connecting a network card allows any MxPro 5 control panel or remote terminal to be networked. All other nodes on the Ad-NeT system will be instantly aware of a panel as soon as it is given a valid network node address, allowing additional panels to be added at any time. All panels incorporate a network analyser providing valuable diagnostic and status information and also have the facility to prevent the transmission of fires or faults during commissioning.

For more complex systems, the Windows-based PC-NeT Mx configuration software allows sector based programming for Mute, Silence, Resound and Reset control keys as well as investigation delays, group disablement and test instructions. All panels within the same sector will share common controls and each panel or remote terminal can also be programmed to show specific network information on a zonal basis. For cause and effect, any input device can be programmed to operate any output device on any panel.


**Mxp-503**
**Mxp-509**

### Features

- Large Ad-NeT+ 200 Panel Network
- Up to 1.5Km between Control Panels
- Windows based PC setup
- Network Systems share up to 1000 zones
- Network Analysis from Control Panel

### Specification

|                                |  |
|--------------------------------|--|
| Network Connections            | IN: A/B SCN(Screen)<br>OUT: A/B SCN (Screen)   |
| On-board Indication            | 2 Red LED's.<br>LED 1 illuminates when data is transmitted<br>LED 2 illuminates when data is received  |
| Supply Current                 | Mxp-503 Standard Network card: 20mA<br>Mxp-509 Fault Tolerant Network Card: 61mA<br>(All power is taken directly from the panel motherboard) |
| Temperature range and Humidity | -5°C to 40C<br>95% non-condensing (maximum)  |
| Dimensions (H x W x D)         | 85mm x 65mm x 20mm<br>(Mounting pillars are provided on the panel chassis to mount this card)  |
| Recommended Cable              | 2 Core twisted-pair plus screen  |

## Order Codes and Options

|           |   |
|-----------|---|
| Mxp-503:  | Standard Network Card   |
| Mxp-509:  | Fault Tolerant Network Card                                   |
| Mxp-503F: | Standard Network Card fitted to a MxPro 5 control panel       |
| Mxp-509F: | Fault Tolerant Network Card fitted to a MxPro 5 control panel |

## Limitations

### Standard Network

The maximum total cable length is 1.5km. The maximum number of network nodes is 32 (50 with signal buffer)

### Fault Tolerant Network

The maximum cable length is 1.5km between each node, and the maximum total loop length is 20km. Each network card has inbuilt diagnostics and is fully monitored for both short and open circuit faults between nodes. The network is capable of withstanding a single fault between nodes without loss of communications to any single panel. The maximum number of network nodes is 200.

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK **T:** +44 (0)345 894 7000, **E:** [enquiries@advancedco.com](mailto:enquiries@advancedco.com),  
**W:** [www.advancedco.com](http://www.advancedco.com)

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.