


4-Way Programmable Relay Card

The Programmable 4-Way Relay Card is an optional peripheral unit that provides four individually programmable relay output circuits.

Up to 16 cards can be connected to a multi-loop control panel providing a maximum of up to 64 additional local relay outputs.

Each output is fully programmable using the powerful dynamic cause-and-effects rules, and all outputs are synchronised.

The unit is available as either a printed circuit card only or as a boxed version with integral 1A power supply.



Applications / Limitations

Plant control and signalling outputs. Each output can be assigned to an individual output group and is fully programmable for any output function allowed within the MxPro 5 configuration program.

Fitting of the Programmable 4-Way Relay Card in a panel precludes fitting of other panel option cards.

Features

- Each output is 230V, 5A rated
- Each output is individually programmable with any of the available dynamic cause-and-effect rules
- Up to 16 cards can be connected providing a total of 64 additional outputs
- Each output may be individually programmed
- An input is provided to monitor the fault output from a power supply.
- 4-way programmable relay card
- Easily configured via PC-NET-003
- 3-year warranty as standard

Specification

| | |
|-----------------------------------|---|
| Applicable Standards | BS EN54-2:1998, BS EN54-4:1998 |
| PCB Dimensions H x W x D mm | 24VDC nominal (18- 28VDC), 22mA (quiescent) 75mA (outputs on) |
| Dimensions H x W x D mm | 100 x 86 x 16 |
| Knockouts 20mm | 7 x top, 2 x bottom |
| AC Supply | 230V AC, 50Hz (+10%, -15%) FUSE T3.15H250 |
| Standby Battery | 2x12V, 7Ah Sealed lead-acid type (Yuasa recommended) |
| LED Indications (Box) | Power and general PSU fault - separate indications of specific PSU fault conditions are available on the PSU. |
| Enclosure | Steel, IP30, RAL9002, 3Kg (excluding batteries) |
| Enclosure Dimensions H x W x D mm | 320 x 345 x 88 |
| LED Indications (PCB) | Relay circuit on, communications TX & RX and heartbeat |
| Outputs (x4) | 230V AC, 5A resistive / 230V AC, ½ HP / 30VDC, 5A |

Order Codes and Options

| | |
|--------------|---|
| MXP-035: | 4-Way Programmable Relay Card |
| MXP-035-BXP: | 4-Way Programmable Relay Card Boxed with 1A PSU |

Compatibility

The Programmable 4-Way Relay Card is compatible with all MxPro 5 control panels.

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK **T:** +44 (0)345 894 7000, **E:** enquiries@advancedco.com,
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.