MxPro4

Advanced Commander - obsolete

The Advanced Commander is a powerful IP based solution for customers requiring protocol translation between their Advanced Fire Control Equipment and a Building Management System (BMS).

The device can be used as a simple bridge between manufacturer's components providing seamless integration and delivering guaranteed performance.

The conversion protocols supported by the Advanced Commander are those generally found in use by the most common Building Management Systems on the market today and are currently 'BACNet' or 'Modbus'.

The Advanced Commander supports up to 640 Objects/Tags of information, which can be configured and passed between network components and delivered to the Building Managements Systems (BMS) using TCP/IP technology.

The Advanced Commander has powerful Windows®based software management suite built-in to provide engineers with the ability to write 'Cause & Effect strategy, check data logging, calendar, and timer functions.

TCP/IP connectivity permits the Advanced Commander to be located locally to the distributed network of Fire Control Panels, but at the same time caters for remote programming and Building Management System (BMS) access.

Features

- BacNet/Modbus Protocol Integration
- 640 Configurable Object/Tags
- Windows® Based Programming
- Powerful IP Controller
- Configurable on a Zone/Point basis per Object for Fire, Fault, Alarm & Isolation
- Engineer configurable over TCP/IP
- Supports a single Ad-Net network
- Small & Compact
- Low Voltage 12vDC - 24vDC
- Configurable using specialized Cause & Effect

Specification

Processor	Embedded AMD Low Power CPU
Memory	512 MB RAM
Disk Space	4Gb Industrial Solid State Hard Drive
Graphics	Not Applicable
Sound Card	Not Applicable
USB Port	Not Applicable
Ethernet	1 x Ethernet Port
Serial Port	2 x Serial port for communication with Ad-Net Networks We recommend ordering the UP-001 (RS232 Cable) for interconnection to Mxp-510-Bx.
PS/2 Socket	Not Applicable
Dimensions	45.0mm(H) x 126mm(W) x 82mm(D)
Power Requirements	1 x Terminal Socket for DC Power Input 12vDC - 24vDC +/- 10% (Not supplied)

Internal Battery	1 x Internal Lithium Battery (Size 1/2AA - 3.6v)
Operating Temperature	0 - 50 Deg C
Warranty	12 Month Warranty

Order Codes and Options

Mxp-642:	Commander - BacNet/ModBus (IP) Interface
Mxp-642C:	Commander - BacNet/ModBus (IP) Interface - Configured
23-PSU/250:	12V Regulated Power Supply Unit
UP-001:	RS232 9-Way to 3-Way cable
Mxp-510-Bx:	Standard Network BMS Interface Boxed
Mxp-510-Bx/FT:	Fault-Tolerant Network BMS Interface Boxed

Compatibility

The Advanced Commander is compatible with all MxPro5 control equipment, but requires the Mxp-510-Bx (BMS/Graphical Interface) to be installed on the Ad-Net network for connectivity to the Commander.

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK T: +44 (0)345 894 7000 E: enquiries@advancedco.com
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.