Axis AX

Intelligent Dual Action Polycarbonate Pull Station

The Advanced Intelligent Dual Action Polycarbonate Pull Station (56000-005ADV) is a low profile, high quality addressable manual pull station. Easily recognizable during a fire situation, the 56000-005ADV station is constructed of rugged polycarbonate for long life and reliability, with a red finish and raised white “FIRE” lettering. A red LED visible through the face of the station flashes during polling and turns on steady in alarm. Each station includes a key-lock for resetting (CAT B / CAT 30) which is common with the Axis AX Series Intelligent Fire Alarm Control Panels.

The 56000-005ADV stations are UL 38 Listed, meet the ADAAG controls and operating guidelines, and the ADA requirements for five pound maximum activation force.

The 56000-005ADV, Intelligent Dual Action Polycarbonate Pull Station, can be mounted semi-flush onto a standard single-gang electrical outlet box. If installations require surface mounting, an optional polycarbonate surface back box (56000-006ADV) is available.

Features

- ADA and ADAAG Compliant
- Dual Action Design
- Rugged Polycarbonate Construction
- Red Status LED
- Easy Key-Lock Reset
- Yellow Activation Stripe

Listings and Approvals

- UL 38 Listed: UNIU.S24867 / ML File: S25235
- ETL ANSI/UL 864 Listed: 101564744NYM-001
- NYCFD COA: #6105A2

Operation

The 56000-005ADV stations are operated by pushing in on the plate marked “PRESS”, and then pulling down on the handle marked “PUSH”, this will latch the handle in the down/activated position. Once latched, a bright yellow activated stripe will appear at the bottom of the station face. To reset the station, simply unlock the station with the reset key (keyed to match Axis AX Series Intelligent Fire Alarm Control Panels) and allow the door to open. This action resets the handle; while closing the door automatically resets the toggle switch to its “STDBY” position.

Wiring Diagram



Specification

Operating Voltage	20-28 VDC, with Communication Pulses 5-9 VDC
Operating Current Quiescent Alarm	 0.2 mA 3.8 mA
Operating Temperature	32ºF (0ºC) to 120ºF (49ºC)
Relative Humidity	10% to 93% Non-Condensing
Dimensions Pull Station Surface Back Box	 5 1/2 ” H x 4 1/4 ” W x 1” D 5 1/2 ” H x 4 1/4 ” W x 1 1/2 ” D
Weight Pull Station Pull Station with Surface Back Box	 7.04 oz 11.5 oz
Analog Value	16 = Normal, 64 = Alarm, 4 = Trouble
Address Range	1 - 126 (DIP Switch Programmable)
Color	Red with Raised White Letters, White “PRESS” and “PUSH” Bars

Order Codes and Options

56000-005ADV	Intelligent Dual Action Polycarbonate Pull Station
56000-006ADV	Polycarbonate Surface Back Box

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK T: +44 (0)345 894 7000 E: enquiries@advancedco.com
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.

Advanced

Axis AX

Intelligent Manual Pull Stations

Advanced Intelligent Manual Pull Stations (AX-APS2) consist of a family of versatile, low profile, and high quality addressable manual pull stations. Easily recognizable during a fire situation, the AX-APS2 stations are constructed of rugged die-cast metal for long life and reliability, with a high gloss red finish and raised white “FIRE” lettering. A red LED on the front of the station flashes during polling and turns on steady in alarm. Integrated into the station is a Form C relay output that activates when in alarm. All models are fitted with a common key-lock for resetting (CAT B / CAT 30) which is common with the panel key.

The AX-APS2 stations are ETL Listed to the ANSI/UL- 38 Standard and have been found to be in compliance with the latest requirements of the Americans with Disabilities Act (ADA). Activation of the pull station meets the requirements for five pound maximum pull force, and the single hand activation.

Available in either single (AX-APS2-F1) or dual (AXAPS2-F2) action configuration, the AX-APS2 stations are designed to prevent false alarms when bumped, jarred or shaken. The dual action AX-APS2-F2 further deters malicious false alarms by requiring a two process function for activation; first push the “PUSH” bar inwards which then allows the “PULL” bar to be grasped and pulled outward.

Optional surface back boxes are available for indoor applications. The Intelligent Manual Pull Stations are available in a variety of colors to meet various special application requirements. Colored stations do not include the raised white “FIRE” labeling, but are capable of accommodating labels for Alert, Alarm, Exit, Evac, etc. identification. Special applications can include; weather alert, door release, medical emergency, fire suppression activation and others.

Operation: The AX-APS2 stations are operated by pulling the handle marked “PULL” on the front of the station as far down as it will go. At this point, the station will lock in place and is easily visible from up to 50 feet away. The activation handle is reset by opening the station with the reset key (keyed to match Axis AX Series Intelligent Fire Alarm Control Panels), returning the toggle switch to its “Normal” position, moving the handle to its upright position and relocking the station. On the AXAPS2-F2 dual station model, the “PUSH” bar must be pushed inward prior to pulling the handle marked “PULL”.

Features

- ADA Compliant
- Single or Dual Action
- Rugged Die-Cast Metal Construction
- Red Status LED
- Integrated Form C Relay Contact
- Low Profile, High Visibility Design
- Visual Indication of Activation including Red Status LED
- Surface or Semi-Flush Mount
- Available in Special Application Colors
- Key-Lock Reset

Listings and Approvals

- ETL ANSI/UL 38 Listed: 3186781NYM-001
- ETL ANSI/UL 864 Listed: 101564744NYM-001
- CSFM Approved: 7165-1713:0101
- NYCFD COA #6105A2





Specification

Operating Voltage	17-28 VDC, with Communication Pulses 5-9 VDC
Operating Current Quiescent Alarm	 1.7 mA 2.7 mA
Operating Temperature	32ºF (0ºC) to 120ºF (49ºC), for Indoor Use Only
Dimensions With Surface Mount Backbox	4 3/4 ” H x 3 1/4 ” W x 1.1” D 4 3/4 ” H x 3 1/4 ” W x 2 1/4 ” D (Cast or Sheet Metal)
Weight	1.1 lb
Analog Value	16 = Normal, 64 = Alarm, 4 = Trouble
Address Range	1 - 126 (DIP Switch Programmable)
Color	Red with Raised White Letters, White “PULL” Bar with Raised Red Letters

Order Codes and Options

AX-APS2-F1	Intelligent Manual Pull Station, Single Action
AX-APS2-F2	Intelligent Manual Pull Station, Dual Action
Options:	
AX-APS-BB1	Interior Surface Mount Backbox - Red (Sheet Metal)
AX-APS-BB1-D	Deep Interior Surface Backbox, Red
AX-APS-BB2	Weatherproof Interior Surface Mount Backbox - Red (Sheet Metal)
AX-APS-BB2-D	Weatherproof Deep Interior Surface Backbox, Red

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK T: +44 (0)345 894 7000 E: enquiries@advancedco.com
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.