Advanced

Axis EN

Single Monitored Input Module

The Axis single input modules are loop powered, designed around a fully digital protocol and allow monitoring of fire alarm and auxiliary devices

The input channel is monitored and will detect Normal / Short / Alarm and Open conditions.

The unit provides fast alarm and fault signalling, and incorporates a bidirectional short circuit isolator.

Connections are made using plug-in terminal blocks which will accept conductors up to 2.5mm².

The unit is supplied fixed to a plate which is suitable for wall mounting with a choice of standard 25mm or deep 47mm mounting boxes available.



Features

- Provides high reliability and error detection
- Short circuit isolators in each device to the requirements of EN54-17
- Large capacity, up to 240 devices per loop
- Auto addressing capability (by the control panel) or manually using a hand held programmer.
- Digital checking of double address
- Line quality information
- Bicolour (red green) LED driven by the control panel

Specification

Power Supply	15-40 V
Average Current Consumption	I=120 uA
LED Current Consumption	Iled=6mA @24Vdc
Operating Temperature Range	-30°C / +70°C
Humidity (non condensing)	95% RH
End-of-Line Resistor	(Reol): 27Kohm
Alarm resistor	(Rw): 10Kohm
Dimensions H x W x D mm	85 x 85 x 30
Weight grams	200
IP Rating	21C

Order Codes and Options

20-VMI100-ADV:	AV Monitored Single Input Module
20-MB100-ADV:	Mounting box 25 mm
20-DMB100-ADV:	Mounting box 47 mm

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK T: +44 (0)345 894 7000 E: enquiries@advancedco.com
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.