Advanced

Axis AX

Enhanced Dual Switch Monitor Module

The Dual Input Monitor Module is a loop-powered device incorporating a dual monitored input circuit for connection to remote switches and is for indoor use only.



Features

- Built-in isolator
- Visible LEDs
- Loop powered
- Ground fault detection
- Selectable priority to monitor equipment where a fast response is required
- Interrupt facility
- Improved design for ease of mounting
- Communicates with XP95 and Discovery protocols

Listings and Approvals

- UL, ULC, SII and CSFM

Specification

General	
Product Operating Temperature	32° to 120° F
Humidity	10% to 93% RH (no condensation or icing)
Standards and Approvals	UL, ULC, SII, CSFM
Dimensions	4.9" W x 4.9" H x 1.175" D
Materials	Housing UL94 V-0 polycarbonate
Wire Size	12-24 AWG
LED Status	
LED Colour: Green Yellow (solid) Red	 Polling Isolation Alarm
Single Line Circuit (SLD) - Supervised Power Limited	
Supply Voltage	17 V to 28 VDC
Modulation Voltage	5 V to 9 V peak to peak
Supervisory Current	500 µA
Switch-on Surge Current	900 µA
Alarm/Operated Current, LED On	1.6 mA per LED
Maximum Loop Current	1 A

Initiating Device Circuit (IDC)	
Wiring Styles	Supervised power limited Class A and Class B
Voltage	3.3 VDC
Line Impedance	100 Ω Max
End-of-line Resistors*	47 kΩ

* A UL-listed end-of-line resistor is available - Part no. 44251-146

NB All data is supplied subject to change without notice. Specifications are typical at 24 V, 73° F and 50% RH unless otherwise stated.

Order Codes and Options

SA4705-720ADV	Enhanced Dual Switch Monitor Module

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK T: +44 (0)345 894 7000 E: enquiries@advancedco.com
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.