Axis EN

Fire Bells

The Advanced Fire Bell is a motorised bell designed for fire alarm applications. Its low current consumption and universally recognisable alarm sound make it an ideal choice for many alarm systems.

Designed for ease of installation, it features a robust steel gong.

Units are finished in Red and are available in two gong sizes, 6" and 8".



Features

- Low current consumption
- Universally recognisable sound
- Diode polarised
- Choice of gong sizes (6 and 8 Inch)
- Approved to:
  - EN54-3:2001 +A1:2002 +A2:2006
  - EN 61000-6-3:2007

Specification

Audibility at 1M	6" Up to 95dB (A) 8" Up to 98dB (A)
Tones	1
Voltage	19-28V_{DC}
Current	20mA
IP Rating	IP21C
Rating	Continuous
Operating Temperature	-10°C to +55°C
Dome Construction	Steel
Weight **6"**	0.92Kg
8"	1.27Kg
Compliance	EN54-3

Order Codes and Options

08-TAA-0007:	6 Inch Red fire bell
08-TAA-0015:	8 Inch Red fire bell

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK T: +44 (0)345 894 7000 E: enquiries@advancedco.com
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.

Axis EN

Weatherproof Fire Bells

The Advanced Weatherproof Fire Bell is a motorised bell designed for fire alarm applications. Its low current consumption and universally recognisable alarm sound make it an ideal choice for many alarm systems.

Designed for ease of installation, it features a robust steel gong.

Units are finished in Red and are available in two gong sizes, 6" and 8"



Features

- Low current consumption
- Universally recognisable sound
- Diode polarised
- Choice of gong sizes (6 and 8 Inch)
- Approved to:
  - EN54-3:2001 +A1:2002 +A2:2006
  - EN 61000-6-3:2007
- Weatherproof to IP33 C

Specification

Audibility at 1M	6": Up to 95dB (A) 8": Up to 98dB (A)
Tones	1
Voltage	19-28 VDC
Current	20mA
IP Rating	IP33C
Rating	Continuous
Operating Temperature	-25°C to +70°C
Dome Construction	Steel
Weight **6"**	0.92Kg
8"	1.27Kg
Compliance	EN54-3

Order Codes and Options

08-TAA-0017:	6 Inch Red weatherproof fire bell
08-TAA-0020:	8 Inch Red weatherproof fire bell

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK T: +44 (0)345 894 7000 E: enquiries@advancedco.com
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.

Axis EN

Remote Indicator Unit

The remote indicator unit is used to give a remote indication of the status of a single or groups of fire detectors in alarm state utilising an LED with a wide area of illumination and high on/off contrast.

The units are compatible with the majority of conventional and addressable systems and can also be used for security and process control applications.

The standard version is a single gang flush mount unit, with or without 'Fire Detector Operated' text and also available with a deep back box for surface mounting.



Features

- Direct fit to a single gang deep back box
- Circular flush mounted version
- Available with text in other languages or without text
- Custom legend available on request
- IP66 weatherproof version available

Specification

Voltage range	5-28 Vdc
Nominal current consumption	24 mA
IP Rating	IP 24
Boxed weight	38 g (flush mount) 95 g (surface mount)
Colour	white (ABS fire retardant plastic)

Order Codes and Options

08-502-003	Remote Indicator Unit
08-502-001	Remote Indicator Unit without Text

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK T: +44 (0)345 894 7000 E: enquiries@advancedco.com
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.