Axis EN

# Remote Indicator Unit

The remote indicator unit is used to give a remote indication of the status of a single or groups of fire detectors in alarm state utilising an LED with a wide area of illumination and high on/off contrast.

The units are compatible with the majority of conventional and addressable systems and can also be used for security and process control applications.

The standard version is a single gang flush mount unit, with or without 'Fire Detector Operated' text and also available with a deep back box for surface mounting.




## Features

- Direct fit to a single gang deep back box
- Circular flush mounted version
- Available with text in other languages or without text
- Custom legend available on request
- IP66 weatherproof version available

## Specification

| | |
|---|---|
| Voltage range | 5-28 Vdc |
| Nominal current consumption | 24 mA |
| IP Rating | IP 24 |
| Boxed weight | 38 g (flush mount) 95 g (surface mount) |
| Colour | white (ABS fire retardant plastic) |

## Order Codes and Options

| | |
|---|---|
| 08-502-003 | Remote Indicator Unit |
| 08-502-001 | Remote Indicator Unit without Text |

Advanced, The Bridges, Balliol Business Park, Newcastle upon Tyne, NE12 8EW, UK T: +44 (0)345 894 7000 E: enquiries@advancedco.com
W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.